


	Customer P/N	Length
RC004317	SA-SFPSMA18-4x	457.2±25mm(18")
RC004318	SA-SFPSMA28-4x	711.2±30mm(28")
RC004319	SA-SFPSMA40-4x	1016±50mm(40")

- CABLE:**
 CONDUCTOR: 30AWG 7/38 SILVER COPPER.
 INSULATION: FLUOROCARBON POLYMER.
 BRAID SHIELD: 5 ENDS 44 AWG TINNED COPPER, 92% MIN. COVERAGE.
 JACKET: FEP BLACK.
 DIAMETER: 0.052" (1.32 mm) NOMINAL.
- CONNECTOR:**
 P1: SFP+ MODULE
 (1)HOOD: ZINC DIE CASTING, NICKEL PLATING.
 (2)LATCH: PC RESIN UL94V, COLOR IN BLACK.
 (3)P.C.B.: 4 LAYERS, FR4. (SPCB-040077A)
 S1~S4: SMA PLUG*4.
- PULL TAB: NYLON UL94V-0, COLOR WHITE.**

4. LABELLING ON BAG:



SFP+(P1)			SMA(S1~S4)	
PIN	SIGNAL		LABEL INFO.	
12	RX-		RX-	
13	RX+		RX+	
18	TX+		TX+	
19	TX-		TX-	
GND			CABLE BRAID	

Serial Cables, LLC

SFP+ TO SMA*4 CABLE

B-3035

SA-SFPSMAxx-4x

Justin

#

mm

11/23/10

DWG\B\3035