



- 1.CABLE SPEC: AMPHENOL SPECTRA-STRIP (166-0099-989)
- (1) 9 PAIRS/ 5 SINGLES
 - (a) 8 PAIRS/ 28 AWG SOLID SILVER PLATED COPPER (DATA)
 - (b) 1 PAIR/ 28 AWG SOLID TINNED COPPER (CREFOLK)
 - (c) 5 SINGLES/ 30 AWG SINGLES 30 AWG SOLID TINNED COPPER
 - (2) OVERALL SHIELD <a> ALUMINIZED POLYESTER, FOIL OUT
 36 AWG TINNED COPPER BRAID, 85% MIN COVERAGE
 - (3) DIAMETER: 8.4mm
- 2.ELECTRICAL: (1) CAPACITANCE: 42 PF/M NOMINAC
(2) IMPEDANCE: 100±5 OHM (DIFFERENTIAL TDR)
(3) PRINT LEGEND: AMPHENOL SPECTRA-STRIP
4X PCIe AWM STYLE 20276 VW-1 80C RoHS COMPLIANT

LENGTH	AWG
500±25	AMPHENOL 28AWG
1000±30	AMPHENOL 28AWG
2000±50	AMPHENOL 28AWG
3000±50	AMPHENOL 28AWG