

WIRING DIAGRAM							
SAS 4i(HOST)			Mini SAS 4i(TARGET)				
rec.	PIN	SIGNAL	plug	PIN	SIGNAL		
P1	2	RX0+	P2	B2	TX0+		
	3	RX0-		B3	TX0-		
	5	TX0-		A3	RX0-		
	6	TX0+		A2	RX0+		
	8	RX1+		B5	TX1+		
	9	RX1-		B6	TX1-		
	11	TX1-		A6	RX1-		
	12	TX1+		A5	RX1+		
	21	RX2+		B13	TX2+		
	22	RX2-		B14	TX2-		
	24	TX2-		A14	RX2-		
	25	TX2+		A13	RX2+		
	27	RX3+		B16	TX3+		
	28	RX3-		B17	TX3-		
	30	TX3-		A17	RX3-		
	31	TX3+		A16	RX3+		
	GND GROUP			GND GROUP			
	1,4,7,10,13			A1,A4,A7,A12,A15,A18			
	20,23,26,29,32			B1,B4,B7,B12,B15,B18			



P/N: SA-8487-XX

**Desc. : Multi-Lane 4i (SFF8484) -
Int. MiniSAS (SFF8087)**

Drawings are property of SerialCables, LLC and for information purposes only. Do Not Edit or Copy