

SAS 4i cable receptacle (HOST) (controller SAS pin assignment)			SATA cable receptacle (TARGET) (device plug pin assignment)		
REC.	PIN	SIGNAL	REC.	PIN	SIGNAL
P0	32	GROUND	P1	1	GROUND
	31	TX3+		2	RX3+
	30	TX3-		3	RX3-
	29	GROUND		4	GROUND
	28	RX3-		5	TX3-
	27	RX3+		6	TX3+
	26	GROUND		7	GROUND
	25	TX2+	P2	1	GROUND
	24	TX2-		2	RX2+
	23	GROUND		3	RX2-
	22	RX2-		4	GROUND
	21	RX2+		5	TX2-
	20	GROUND		6	TX2+
	19	SIDEBAND 5		7	GROUND
	18				
	17				
	16				
	15				
	14	SIDEBAND 0	P3	1	GROUND
	13	GROUND		2	RX1+
	12	TX1+		3	RX1-
	11	TX1-		4	GROUND
	10	GROUND		5	TX1-
	9	RX1-		6	TX1+
	8	RX1+		7	GROUND
	7	GROUND	P4	1	GROUND
	6	TX0+		2	RX0+
	5	TX0-		3	RX0-
	4	GROUND		4	GROUND
	3	RX0-		5	TX0-
	2	RX0+		6	TX0+
	1	GROUND		7	GROUND



P/N: SA-84S7P-XX

Desc. : 4i Mult-lane (SFF-8484) - SATA (4x)

Drawings are property of Serial Cables, LLC and for information purposes only. Do Not Edit or Copy