

**MATERIAL RoHS COMPLIANT:****CABLE:**

CONDUCTOR: 28AWG SOLID SILVER PLATED COPPER.
INSULATION: FOAM POLYOLEFIN.

PAIR: 2 SINGLES LAID FLAT AND PARALLEL.

PAIR DRAIN WIRE: 30AWG SOLID SILVER PLATED COPPER.

PAIR SHIELD: ALUMINUM/POLYESTER TAPE. ALUMINUM SIDE FACING IN, 25% OVERLAP.

INNER SHIELD: ALUMINUM/POLYESTER TAPE, ALUMINUM SIDE PACING OUT, 25% OVERLAP.

OUTER SHIELD: 38AWG TIN PLATED COPPER BRAID, 85% COVERAGE.

DIAMETER: $\phi 4.7$ mm NOMINAL. COLOR: BLACK.

PRINT LEGEND: "MADISON CABLE CORP. TYPE CL2 75°C 28AWG (UL) TurboTwin™"

DIFFERENTIAL IMPEDANCE: 100 ± 5 OHMS @TDR

UL LISTING: TYPE CL2 AS SPECIFIED IN ARTICLE 725 OF THE NATIONAL ELECTRICAL CODE. TURBO TWIN™

CONNECTOR:

P0~P4: Mini SAS 4X CABLE PLUG - 26CKT CONNECTOR(SFF-8088)

(1) P.C.B: FR4, 4 LAYERS

(2) LATCH: STAINLESS STEEL

(3) BACKSHELL- ZINC DIE CASTING HOOD/ NICKEL PLATING

(4) WITH EXTERNAL UNIVERSAL KEY



P/N: SA-8888-8888888888 **Desc. :** 2x MiniSAS (SFF-8088) - 4x MiniSAS (SFF-8088)